

## Acetone

179973-1L

Version 1.5

Revision Date 24.01.2021

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : Acetone  
SDS-number : 000000020241  
Type of product : Substance  
Remarks : SDS according to Art. 31 of Regulation (EC) 1907/2006.

Chemical name : acetone; propan-2-one; propanone  
Index-No. : 606-001-00-8  
REACH Registration Number : no data available

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Laboratory chemicals  
Uses advised against : none

#### 1.3. Details of the supplier of the safety data sheet

Company : Honeywell Specialty Chemicals Seelze GmbH  
Wunstorfer Straße 40  
30926 Seelze  
Germany  
Telephone : (49) 5137-999 0  
For further information, please contact: : PMTEU Product Stewardship:  
SafetyDataSheet@Honeywell.com  
Honeywell International, Inc.  
115 Tabor Road  
Morris Plains, NJ 07950-2546  
USA

#### 1.4. Emergency telephone number

Emergency telephone number : +1-703-527-3887 (ChemTrec-Transport)  
+1-303-389-1414 (Medical)  
Country based Poison Control Center : see chapter 15.1

**Acetone**

179973-1L

Version 1.5

Revision Date 24.01.2021

**SECTION 2: Hazards identification**


**2.1. Classification of the substance or mixture**

**REGULATION (EC) No 1272/2008**

Flammable liquids Category 2  
H225 Highly flammable liquid and vapour.  
Eye irritation Category 2  
H319 Causes serious eye irritation.  
Specific target organ toxicity - single exposure Category 3 - Central nervous system  
H336 May cause drowsiness or dizziness.

**2.2. Label elements**

**REGULATION (EC) No 1272/2008**

Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. EUH066 Repeated exposure may cause skin dryness or cracking.
Precautionary statements	:	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. P280 Wear protective gloves/ eye protection/ face protection. P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308 + P313 IF exposed or concerned: Get medical advice/ attention.

## Acetone

179973-1L

Version 1.5

Revision Date 24.01.2021

### 2.3. Other hazards

Highly flammable. May cause drowsiness or dizziness. Take measures to prevent the build up of electrostatic charge.

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Chemical name	CAS-No. Index-No. REACH Registration Number EC-No.	Classification 1272/2008	Concentration	Remarks
acetone; propan-2-one; propanone	67-64-1 606-001-00-8 200-662-2	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066	100 %	

### 3.2. Mixture

Not applicable

Occupational Exposure Limit(s), if available, are listed in Section 8.  
For the full text of the H-Statements mentioned in this Section, see Section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

*General advice:*

First aider needs to protect himself. Move out of dangerous area. Take off all contaminated clothing immediately.

*Inhalation:*

Remove to fresh air. Keep patient warm and at rest. If symptoms persist, call a physician.

*Skin contact:*

After contact with skin, wash immediately with plenty of water. Call a physician if irritation develops or persists.

*Eye contact:*

## Acetone

179973-1L

Version 1.5

Revision Date 24.01.2021

---

Rinse thoroughly with plenty of water, also under the eyelids. Protect unharmed eye. Consult a physician.

*Ingestion:*

When swallowed, allow water to be drunk. Do NOT induce vomiting. Call a physician immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

No data available

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

See Section 11 for more detailed information on health effects and symptoms.

---

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

*Suitable extinguishing media:*

Water spray  
Foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry powder

*Extinguishing media which shall not be used for safety reasons:*

High volume water jet

### 5.2. Special hazards arising from the substance or mixture

Vapours may form explosive mixtures with air.  
Heating will cause pressure rise with risk of bursting and subsequent explosion  
In case of fire hazardous decomposition products may be produced such as:  
Carbon monoxide  
Carbon dioxide (CO<sub>2</sub>)

**Acetone**

179973-1L

Version 1.5

Revision Date 24.01.2021

---

**5.3. Advice for firefighters**

In the event of fire, wear self-contained breathing apparatus.  
Apply foam in large quantities because some of it will be destroyed by the product. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

---

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation.

**6.2. Environmental precautions**

Do not flush into surface water or sanitary sewer system.

**6.3. Methods and materials for containment and cleaning up**

Soak up with inert absorbent material.  
Pick for disposal in tightly closed containers

**6.4. Reference to other sections**

For personal protection see section 8.

---

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

*Advice on safe handling:*

Exhaust ventilation at the object is necessary. Use explosion-proof equipment. Provide sufficient air exchange and/or exhaust in work rooms.

*Advice on protection against fire and explosion:*

The heavy vapours can overcome a considerable distance up to the source of ignition. Take measures to prevent the build up of electrostatic charge. Keep away from sources of ignition - No smoking.

*Hygiene measures:*

Take off all contaminated clothing immediately. Recommended preventive skin protection

**7.2. Conditions for safe storage, including any incompatibilities**

*Further information on storage conditions:*

**Acetone**

179973-1L

Version 1.5

Revision Date 24.01.2021

Store in original container. Keep containers tightly closed in a dry, cool and well-ventilated place.  
Recommended storage temperature: 10 - 25 °C.

**7.3. Specific end use(s)**

no additional data available

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limits:**

Components	Basis / Value type	Value / Form of exposure	Exceeding Factor	Remarks
acetone; propan-2-one; propanone	EH40 WEL STEL	3.620 mg/m <sup>3</sup> 1.500 ppm		
acetone; propan-2-one; propanone	EH40 WEL TWA	1.210 mg/m <sup>3</sup> 500 ppm		
acetone; propan-2-one; propanone	EU ELV TWA	1.210 mg/m <sup>3</sup> 500 ppm		Indicative

STEL - Short term exposure limit  
TWA - Time weighted average

**DNEL/ PNEC-Values**

Component	End-use/impact	Exposure duration	Value	Exposure routes	Remarks
acetone; propan-2-one; propanone	Workers / Long-term systemic effects		1210 mg/m <sup>3</sup>	Inhalation	
acetone; propan-2-one; propanone	Workers / Long-term systemic effects		62mg/kg bw/d	Ingestion	
acetone; propan-2-one; propanone	Workers / Long-term systemic effects		186mg/kg bw/d	Skin contact	
acetone; propan-2-one; propanone	Consumers / Long-term		200 mg/m <sup>3</sup>	Inhalation	

**Acetone**

179973-1L

Version 1.5

Revision Date 24.01.2021

	systemic effects				
acetone; propan-2-one; propanone	Workers / Acute local effects		2420 mg/m <sup>3</sup>	Inhalation	
acetone; propan-2-one; propanone	Consumers / Long-term systemic effects		62mg/kg bw/d	Skin contact	

Component	Environmental compartment / Value	Remarks
acetone; propan-2-one; propanone	Fresh water: 10,6 mg/l	
acetone; propan-2-one; propanone	Marine water: 1,06 mg/l	
acetone; propan-2-one; propanone	Fresh water sediment: 30,4 mg/l	
acetone; propan-2-one; propanone	Marine sediment: 3,04 mg/l	
acetone; propan-2-one; propanone	Soil: 29,5 mg/l	
acetone; propan-2-one; propanone	Sewage treatment plant: 100 mg/l	

**8.2. Exposure controls**

**Occupational exposure controls**

Do not breathe vapours/dust.

The Personal Protective Equipment must be in accordance with EN standards:respirator EN 136, 140, 149; safety glasses EN 166; protective suit: EN 340, 463, 468, 943-1, 943-2; gloves EN 374, 511; safety shoes EN-ISO 20345.

**Personal protective equipment**

*Respiratory protection:*

In the case of vapour formation use a respirator with an approved filter.

Recommended Filter type:

Organic gas and low boiling vapour type

*Hand protection:*

Glove material: butyl-rubber

Break through time: > 480 min

Glove thickness: 0,7 mm

Butoject® 898

Gloves must be inspected prior to use.

## Acetone

179973-1L

Version 1.5

Revision Date 24.01.2021

Replace when worn.

Remarks: Supplementary note: The specifications are based on information and tests from similar substances by analogy.

Due to varying conditions ( e.g.temperature or other strains) it must be considered that the usage of a chemical protective glove in practice may be much shorter than the permeation time determined in accordance with EN 374.

Since actual conditions of practical use often deviate from standardised conditions according EN 374 the glove manufacturer recommends to use the chemical protective glove in practice not longer than 50% of the recommended permeation time.

Manufacturer's directions for use should be observed because of great diversity of types .

Suitable gloves tested according EN 374 are supplied e.g. from KCL GmbH, D-36124 Eichenzell, Vertrieb@kcl.de

*Eye protection:*

Safety goggles

*Skin and body protection:*

Protective suit

### Environmental exposure controls

Handle in accordance with local environmental regulations and good industrial practices.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	:	liquid
Colour	:	colourless
Odour	:	characteristic
Melting point/range	:	-95 °C
Boiling point/boiling range	:	55 - 57 °C at 1.013 hPa
Upper explosion limit	:	14,3 %(V)
Lower explosion limit	:	2,2 %(V)
Flash point	:	-17 °C Method: closed cup



**Acetone**

179973-1L

Version 1.5

Revision Date 24.01.2021

---

Ignition temperature : 465 °C  
Method: DIN 51794

Decomposition temperature : 236 °C

pH : Not applicable

Auto-ignition temperature : not auto-flammable

Viscosity, kinematic : No data available

Water solubility : completely miscible

Partition coefficient: n-  
octanol/water : log Pow -0,24

Vapour pressure : ca. 240 hPa  
at 20 °C

Vapour pressure : 580 hPa  
at 50 °C

Density : 0,79 g/cm<sup>3</sup>  
at 20 °C

Relative vapour density : No data available

**9.2 Other Information**

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Evaporation rate : No data available

Viscosity, dynamic : 0,32 mPa.s  
at 20 °C

---

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

Stable under normal conditions.

## Acetone

179973-1L

Version 1.5

Revision Date 24.01.2021

---

### 10.2. Chemical stability

236 °C  
Decomposition temperature  
At normal pressure may be distilled without decomposition.

### 10.3. Possibility of hazardous reactions

Reacts with air to form peroxides.  
Vapours may form explosive mixture with air.

### 10.4. Conditions to avoid

None known.

### 10.5. Incompatible materials

Plastic materials can be attacked.  
Strong oxidizing agents  
Bases  
Strong acids  
Alkali metals  
Alkaline earth metals

### 10.6. Hazardous decomposition products

No decomposition if stored and applied as directed.

---

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

*Acute oral toxicity:*

LD50

Species: Rat

Value: 5.800 mg/kg

*Acute dermal toxicity:*

LD50

Species: Rat

Value: > 7.400 mg/kg

*Acute inhalation toxicity:*

LC50

Species: Rat

## Acetone

179973-1L

Version 1.5

Revision Date 24.01.2021

---

Value: 76 mg/l  
Exposure time: 4 h

*Skin irritation:*  
Species: Rabbit  
Classification: slightly irritant  
Method: Draize Test

*Eye irritation:*  
Species: Rabbit  
Classification: Severe eye irritation

*Respiratory or skin sensitisation:*  
Species: Guinea pig  
Classification: non-sensitizing

*Repeated dose toxicity:*  
Species: Rat, male  
Application Route: Oral  
Exposure time: 90 d  
NOAEL 900 mg/kg  
Method: OECD Test Guideline 408

*Aspiration hazard:*  
No data available

### 11.2. Information on other hazards

Endocrine disrupting properties  
No data available

*Other information:*  
Solvent removes skin oil from the skin.  
Inhalation of acetone can cause headaches and a dazed state. Alcohol increases this effect.

---

## SECTION 12: Ecological information

### 12.1. Toxicity

*Toxicity to fish:*  
LC50  
Species: Pimephales promelas (fathead minnow)  
Value: 6.210 mg/l  
Exposure time: 96 h

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**Honeywell**

## Acetone

179973-1L

Version 1.5

Revision Date 24.01.2021

---

### LC50

Species: *Leuciscus idus* (Golden orfe)

Value: 11.300 mg/l

Exposure time: 48 h

### LC50

Species: *Gambusia affinis* (Mosquito fish)

Value: 13.000 mg/l

Exposure time: 48 h

### LC50

Species: *Oncorhynchus mykiss* (rainbow trout)

Value: 5.540 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

### *Toxicity to aquatic plants:*

#### EC50

Species: Algae

Value: 3.400 mg/l

Exposure time: 48 h

### *Toxicity to Microorganisms:*

#### EC50

Species: Bacteria

Value: 1.700 mg/l

Exposure time: 16 h

### *Toxicity to aquatic invertebrates:*

#### LC50

Species: *Daphnia pulex* (Water flea)

Value: 8.800 mg/l

Exposure time: 48 h

#### NOEC

Species: *Daphnia magna* (Water flea)

Value: 2.212 mg/l

Exposure time: 48 h

Method: OECD Guideline No. 211

## 12.2. Persistence and degradability

### *Biodegradability:*

Biodegradation: 90 %

Exposure time: 28 d

**Acetone**

179973-1L

Version 1.5

Revision Date 24.01.2021

---

Result: Readily biodegradable

**12.3. Bioaccumulative potential**

Bioconcentration factor (BCF): 3  
Bioaccumulation is unlikely.

**12.4. Mobility in soil**

No data available

**12.5. Results of PBT and vPvB assessment**

No data available

**12.6. Endocrine disrupting properties**

No data available

**12.7. Other adverse effects**

Biochemical Oxygen Demand (BOD) : Value: 1.760 mg/g  
Chemical Oxygen Demand (COD) : Value: 2.070 mg/g

---

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

*Product:*  
Dispose according to legal requirements.

*Packaging:*  
Legal requirements are to be considered in regard of reuse or disposal of used packaging materials

*Further information:*  
Provisions relating to waste:  
EC Directive 2006/12/EC; 2008/98/EEC  
Regulation No. 1013/2006

For personal protection see section 8.

---

**SECTION 14: Transport information**

**14.1 UN number**

**Acetone**

179973-1L

Version 1.5

Revision Date 24.01.2021

ADR/RID:1090

IMDG:1090

IATA:1090

**14.2 UN proper shipping name**

ADR/RID:ACETONE

IMDG:ACETONE

IATA:Acetone

**14.3 Transport hazard class(es)**

ADR/RID: 3

IMDG: 3

IATA: 3

**14.4 Packaging group**

ADR/RID: II

IMDG: II

IATA: II

**14.5 Environmental hazards**

ADR/RID:no

Marine pollutant: no

**14.6 Special precautions for user**

No data available

**14.7 Maritime transport in bulk according to IMO instruments**

No data available

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Basis	Value	Remarks
Directive 2012/18/EC Listed in Regulation : P5c: FLAMMABLE LIQUIDS Number in Regulation: 1.2.5.3	<b>Quantity:</b> 5.000.000 kg <b>Quantity:</b> 50.000.000 kg	
Substances of very high concern (SVHC)		This product does not contain substances of very high concern according to Regulation (EC) No Article 57 above the respective regulatory 1907/2006 (REACH), concentration limit of $\geq 0.1\%$ (w/w).
Regulation (EU) 2019/1148 on the marketing and use of explosives precursors		Contains components listed in

**Acetone**

179973-1L

Version 1.5

Revision Date 24.01.2021

**Poison Control Center**

Country	Phone Number
Austria	+4314064343
Belgium	070 245245
Bulgaria	(+)35929154233
Croatia	(+3851)23-48-342
Cyprus	+357 2240 5611
Czech Republic	+420224919293; +420224915402
Denmark	82121212
Estonia	16662; (+372)6269390
Finland	9471977
France	+33(0)145425959
Greece	+30 210 779 3777
Hungary	(+36-80)201-199
Iceland	5432222
Ireland	+353(1)8092166
Italy	0382 24444
Germany	Berlin : 030/19240
	Bonn : 0228/19240
	Erfurt : 0361/730730
	Freiburg : 0761/19240
	Göttingen : 0551/19240
	Homburg : 06841/19240
	Mainz : 06131/19240
Munich : 089/19240	
Latvia	+37167042473

Country	Phone Number
Liechtenstein	+41 442515151
Lithuania	+370532362052
Luxembourg	070245245; (+352)80002-5500
Malta	+356 2395 2000
Netherlands	030-2748888
Norway	22591300
Poland	+48 42 25 38 400
Portugal	808250143
Romania	+40 21 318 3606
Slovakia (NTIC)	+421 2 54 774 166
Slovenia	+386 1 400 6051
Spain	+34915620420 112 (begär Giftinformation);+46104566786
Sweden	112 (begär Giftinformation);+46104566786
Switzerland	145
United Kingdom	(+44) 844 892 0111

**Other inventory information**

US. Toxic Substances Control Act  
On TSCA Inventory

Australia. Industrial Chemical (Notification and Assessment) Act  
On the inventory, or in compliance with the inventory

## Acetone

179973-1L

Version 1.5

Revision Date 24.01.2021

Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL)  
All components of this product are on the Canadian DSL

Japan. Kashin-Hou Law List  
On the inventory, or in compliance with the inventory

Korea. Existing Chemicals Inventory (KECI)  
On the inventory, or in compliance with the inventory

Philippines. Inventory of Chemicals and Chemical Substances (PICCS)  
On the inventory, or in compliance with the inventory

China. Inventory of Existing Chemical Substances (IECSC)  
On the inventory, or in compliance with the inventory

New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand  
On the inventory, or in compliance with the inventory

### 15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

### Text of H-statements referred to under heading 3

acetone; propan-2-one; propanone	:	H225	Highly flammable liquid and vapour.
		H319	Causes serious eye irritation.
		H336	May cause drowsiness or dizziness.
		EUH066	Repeated exposure may cause skin dryness or cracking.

### Further information

All directives and regulations refer to amended versions.  
Vertical lines in the left hand margin indicate a relevant amendment from the previous version.

Abbreviations:

EC European Community  
CAS Chemical Abstracts Service



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**Honeywell**

## Acetone

179973-1L

Version 1.5

Revision Date 24.01.2021

---

DNEL Derived no effect level  
PNEC Predicted no effect level  
vPvB Very persistent and very bioaccumulative substance  
PBT Persistent, bioaccumulative und toxic substance

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user.

This information should not constitute a guarantee for any specific product properties.

---